

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

International Patent Classification <sup>6</sup> :**H04N 7/173****A1**

(11) International Publication Number:

**WO 98/47283**

(43) International Publication Date:

22 October 1998 (22.10.98)

International Application Number: **PCT/US97/17031**

International Filing Date: 23 September 1997 (23.09.97)

Priority Data:

60/043,539

14 April 1997 (14.04.97)

**US**

Applicant (for all designated States except US): THOMSON CONSUMER ELECTRONICS, INC. [US/US]; 10330 North Meridian Street, Indianapolis, IN 46290-1024 (US).

Inventors; and

Inventors/Applicants (for US only): WEHMEYER, Keith, Reynolds [US/US]; 6411 Columbia Circle, Fishers, IN 46038 (US). LOGAN, Robert, Joseph [US/US]; 4302 Sagamore Trail, Indianapolis, IN 46220 (US). COMER, Robert, Skipworth [US/US]; 103 East 106th Street, Indianapolis, IN 46280 (US). CROSBY, Sheila, Renee [US/US]; 325 Hampton Court, Crystal Lake, IL 60012 (US).

Agents: TRIPOLI, Joseph, S. et al.; GE AND RCA Licensing Management Operation Inc., P.O. Box 5312, Princeton, NJ 08543 (US).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).


Published

With international search report.

Title: SYSTEM FOR COLLATING DATA FROM MULTIPLE SOURCES TO FORM A COMPOSITE PROGRAM GUIDE FOR DISPLAY

## Abstract

A video decoder system collates program guide information acquired from a variety of local and remote sources (5, 415, 420). Program guide information is received from first source and a selectable program guide menu icon is played. A category of program guide information items from the first source is collated (425) by a display attribute response to selection of the menu icon and the collated program guide information items are displayed (430, 435). The display attribute allocated to the category of program guide information items is common to both the category of items and to the menu icon. Codes identifying program categories may be converted to other codes using equivalence mapping information for classifying programs according to a master set of program categories (425). Composite program guide information may be formed including new data identifiers allocated to program guide information items for use in retrieving the items from a second source (420).



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

Albania	ES	Spain	LS	Lesotho	SI	Slovenia
Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
Austria	FR	France	LU	Luxembourg	SN	Senegal
Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
Brazil	IL	Israel	MW	Malawi	UG	Uganda
Belarus	IS	Iceland	MX	Mexico	US	United States of America
Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
Cameroon	KR	Republic of Korea	PT	Portugal		
China	KZ	Kazakhstan	RO	Romania		
Cuba	LC	Saint Lucia	RU	Russian Federation		
Czech Republic	LI	Liechtenstein	SD	Sudan		
Germany	LK	Sri Lanka	SE	Sweden		
Denmark	LR	Liberia	SG	Singapore		
Estonia						

## System for Collating Data From Multiple Sources to Form a Composite Program Guide for Display

5        This is a non-provisional application of provisional application serial No. 60/043,539 by R. J. Logan et al, filed 14 April 1997.

### *Field of the Invention*

10        This invention is related to the field of digital signal processing, and more particularly to the acquisition, formation and processing of Program Guide Information, and program content data, derived from multiple sources, e.g. Internet, cable, satellite and terrestrial sources.

15

### *Background of the Invention*

Home entertainment systems which combine Personal Computer and television functions (PC/TV systems), are  
20 increasingly becoming, generic, User interactive, multiple source and multiple destination communication devices. Such systems are required to communicate in different data formats between multiple locations for a variety of applications in response to User requests. For example, a PC/TV system may receive data from  
25 satellite or terrestrial sources comprising High Definition Television (HDTV) broadcasts, Multi-point Microwave Distribution System (MMDS) broadcasts and Digital Video Broadcasts (DVB). A PC/TV system may also receive and transmit data via telephone (e.g. the Internet) and coaxial lines (e.g. cable TV) and from both  
30 remote and local sources such as Digital Video Disk (DVD), CDROM, VHS and Digital VHS (DVHS™) type players, PCs, and many other types of sources.

A number of problems arise in developing such a generic PC/TV entertainment system. Specifically, problems arise  
35 in supporting communication between multiple data sources and in processing data from the multiple sources. A problem is also presented by the need to devise a User interface for such a system

that supports complex User interactive tasks whilst providing a simple command interface suitable for the general public. A PC/TV system User interface, for example, should allow a User to view a selected program and permit User operation of functions such as Email, telephone, Internet access, fax and video-phone functions. Such applications require communication between a PC/TV unit and a variety of both remote sources e.g. a satellite service provider, and local sources e.g. a DVD storage device. Further, a PC/TV needs to process and decode data in different data formats from different devices and display received data to the User. These problems are addressed by a system according to the present invention.

### *Summary of the Invention*

15

The inventors have hereby recognized that a Program Guide type of User interface advantageously provides a simple, easy to use interface for User operation of functions such as Email, telephone, Internet access, fax, home control, and video-phone functions. The use of a Program Guide for such functions also advantageously provides a single User interface for User operation of multiple devices and associated functions.

The inventors have further recognized that it is desirable for a video decoder system to be capable of collating program guide information acquired from a variety of local and remote sources. Specifically, the inventors have recognized that the information may be advantageously collated into categories of items for display in accordance with a) allocated display attributes e.g. color, shading, or shape, b) allocated data identifiers e.g. packet identifiers (PIDs), c) hierarchical program content structures e.g. a theme encompassing subtopics (such as movies classified by comedy, horror etc.), d) equivalence mapping information that maps a received set of program categories to a defined superset of categories, and e) characteristics including the source, function and content of a program guide item.

In a method for collating program guide information received from a first source, a selectable program guide menu icon

3

is displayed. A category of program guide information items from the first source is collated by a display attribute in response to selection of the menu icon and the collated program guide information items are displayed. The display attribute allocated to  
5 the category of program guide information items is common to both the category of items and to the menu icon.

In a feature of the invention, composite program map information is formed including a new data identifier allocated to a program guide information item and the new identifier is used  
10 to retrieve the item from a second source.

In another feature of the invention, a first code identifying a program category is converted to a second code using equivalence mapping information for classifying programs according to a master set of program categories.

15

### *Brief Description of the Drawings*

In the drawing:

Figure 1 shows a home entertainment decoder system, according to the invention, for communicating with a plurality of  
20 sources and for processing program guide information and program content data.

Figure 2 shows an exemplary Program Guide display  
25 format according to the invention.

Figure 3 shows a data format, according to the invention, for packetizing Internet data for transmission within an MPEG compatible datastream.

30

Figure 4 shows a flowchart, according to the invention, for receiving program guide information including User selection options and processing the received information to form a program guide supporting User selectable communication  
35 functions.

4

Figure 5 shows a flowchart, according to the invention, for a process to form a program guide in a video decoder from information received from a plurality of sources.

5           Figure 6 shows a flowchart, according to the invention, for a process to automatically acquire and collate program guide information from a plurality of sources and to form a program guide for display.

10           Figure 7 shows a black and white representation of an exemplary color Program Guide display format, according to the invention, showing menu options permitting a User to collate programs by source and color attribute.

15           Figure 8 shows a flowchart, according to the invention, for a process to acquire information requested by a video receiver User via a selection made from options on a displayed program guide.

20           Figure 9 shows a flowchart, according to the invention, for a process to decode input Internet information and compressed video data and to form a composite video output for display.

## 25           *Detailed Description of the Drawings*

Figure 1 shows a home entertainment decoder system, according to the invention, for communicating with multiple sources to acquire program guide information and program  
30 content data. The decoder system forms a program guide for display from information acquired and collated automatically from multiple sources. A User may initiate Email, telephone, Internet access, fax and video-phone functions via selection of options from the displayed program guide. The decoder system adaptively  
35 decodes a datastream encoded to the MPEG standard incorporating compressed program content data and Internet data representative of, for example, Hypertext Mark-up Language

(HTML). The decoded data is formatted either as a composite video image or as separate video images for display.

The MPEG2 (Moving Pictures Expert Group) image encoding standard, hereinafter referred to as the "MPEG standard" is comprised of a system encoding section (ISO/IEC 13818-1, 10th June 1994) and a video encoding section (ISO/IEC 13818-2, 20th January 1995), hereinafter referred to as the "MPEG systems standard" and "MPEG video standard" respectively.

Although the disclosed system is described in the context of a system for receiving an MPEG compatible signal, it is exemplary only. The principles of the invention may be applied to systems in which the types of transmission channels and communication protocols may vary, or to systems in which the coding type may vary. Such systems may include, for example, non-MPEG compatible systems, involving other types of encoded datastreams and other methods of conveying Program Guide information. Further, although the disclosed system is described as processing broadcast programs, this is exemplary only. The term 'program' is used to represent any form of data such as telephone messages, computer programs, Internet data or other communications, for example.

In overview, in the video receiver system of Figure 1, a carrier modulated with video data is received from a broadcast satellite by antenna 10 and processed by unit 15. The resultant digital output signal is demodulated by demodulator 20 and decoded and error corrected by decoder 30. In this exemplary embodiment, the demodulated and decoded output from unit 30 is in the form of an MPEG compatible transport stream containing MPEG compressed video data and Internet data encoded in HTML. Video data encoded to the MPEG standard is in the form of a packetized datastream which typically includes the data content of many program channels (e.g. content corresponding to cable television channels 1-125).

The MPEG compatible transport stream is provided to processor 25 which is responsive to commands from remote control unit 125. Processor 25 communicates with other data sources including storage device 90 and either Internet data

server 83 or Internet connection service 87 (e.g. America On-line™). Program guide information is acquired and collated automatically from the input transport stream and storage device 90 and either server 83 or connection service 87. The acquired  
5 information is merged by processor 25 to form a program guide for display incorporating selection options allowing a User to initiate Email, telephone, Internet access, fax and video-phone functions among others, for example. The program guide for display is also formed to include non-displayed information from  
10 multiple sources for identifying and assembling individual data packets that constitute the programs that are selected for User viewing or listening. This information is used in recovering the content of selected programs from multiple sources.

Processor 25 adaptively decompresses the input  
15 compressed video data and decodes the HTML Internet data to provide a formatted composite video image for display on unit 75. Processor 25 also provides encoded data outputs for storage on storage medium 105 via storage device 90, and provides encoded data to other devices (not shown to simplify drawing) via modem  
20 80 and telephone lines.

A video receiver user initiates functions including Email, telephone, Internet access, fax and video-phone functions and viewing and storage of selected programs via selection of options from the displayed program guide. A User selects a  
25 displayed option with a cursor using remote control unit 125. Commands from remote control 125 are passed via interface 120 to controller 115 within processor 25. Unit 115 controls the operation of the elements of processor 25 and responds to remote control unit 125 commands using a bi-directional data and control  
30 signal bus C. Controller 115 controls the functions of individual elements within processor 25 by setting control register values within these elements with control bus C. Processor 25 also supports the storage and retrieval of data from storage medium 105 via storage device 90. Storage device 90 is a DVD type device  
35 and medium 105 comprises a multi-disk stack unit containing a plurality of disks in this exemplary embodiment.

Considering Figure 1 in detail, a carrier modulated with video data received by antenna 10, is converted to digital form and processed by input processor 15. Processor 15 includes radio frequency (RF) tuner and intermediate frequency (IF) mixer and amplification stages for down-converting the input video signal to a lower frequency band. Processor 15 also includes an analog to digital converter for digitizing the down-converted signal to produce a signal suitable for further processing. The resultant digital output signal is demodulated by demodulator 20 and decoded and error-corrected by decoder 30. The output from decoder 30 is further processed by unit 45 of processor 25.

The data provided to unit 45 is in the form of an MPEG compliant packetized transport datastream as defined in MPEG systems standard section 2.4 and includes program guide information and the data content of one or more program channels. Processor 25 acquires and collates program guide information automatically from the input transport stream and storage device 90 and either Internet data server 83 or Internet connection service 87 (e.g. America On-line™). The individual packets that comprise either particular program channel content, or Program Guide information, are identified by their Packet Identifiers (PIDs) contained within header information.

In response to control signal C, unit 45 selects either the transport stream from unit 30, or in a playback mode, a datastream retrieved from storage device 90 via store interface 95. In normal, non-playback operation, individual packets that comprise program guide information are identified by unit 45 in the transport stream from unit 30 and assembled using PIDs that are predetermined and stored in internal memory of controller 115. Unit 45 matches the PIDs of incoming packets in the transport datastream from decoder 30 with PID values pre-loaded in control registers within unit 45 by controller 115. Therefore, satellite broadcast program guide (SPG) information packets in the transport stream are identified by unit 45 without additional PID information. Controller 115 acquires a full SPG by accessing and assembling the SPG packets that are identified and captured by unit 45.

The PID information that enables controller 115, in conjunction with unit 45, to identify data packets that comprise individual programs is termed a program or channel map. The program map associates PIDs with individual packetized datastreams that constitute a program and is part of the SPG. The SPG may also contain additional information, e.g. packet assembly information, supporting the recovery of program guide data from the input transport stream.

Controller 115 also configures unit 45 using Control signal C to select the data packets comprising the DVD program guide (DPG) information derived from DVD storage device 90 via interface 95. Unit 45 matches the PIDs of incoming packets in the packet datastream from interface 95 with PID values pre-loaded in control registers within unit 45 by controller 115. Controller 115 acquires a full DPG by accessing and assembling the DPG packets that are identified and captured by unit 45.

A similar process is followed in acquiring Internet program guide (IPG) information from Internet server 83 or from Internet connection service 87 by telephone line communication via modem 80. In acquiring the IPG, data identifiers analogous to or the same as the PIDs used in acquiring the SPG or DPG are matched with identifiers pre-loaded by controller 115. The matching function may be performed either within unit 80 or by controller 115. The process for acquiring program guide information is explained in greater detail in the description of Figures 4-6.

The SPG, DPG and IPG information acquired by controller 115 is merged by processor 25 to form a program guide for display incorporating selection options allowing a User to initiate Email, telephone, Internet access, fax and video-phone functions. In merging the data, the acquired SPG, DPG and IPG information is collated into two levels of hierarchy termed theme and topic and redundant program guide information is eliminated. A theme, for example, may include categories such as movies, sports, weather, arts, documentaries, news, etc. A topic is a category within a theme, for example, a movie theme category may have topics including, comedy, thriller, horror, science fiction,

romance, adult entertainment, etc. Different or additional levels of hierarchy may be used in collating the acquired SPG, DPG and IPG information involving criteria such as viewer age suitability, the period setting e.g. contemporary or historical, reviewer ratings etc.

5           A number of problems occur in collating the SPG, DPG and IPG information. The SPG, DPG and IPG information, being from different sources, may categorize programs by different themes and topics and may use a different sorting hierarchy. Further, the SPG, DPG and IPG data may use conflicting, redundant  
10 or incompatible PIDs or other data identifiers for identifying individual data elements that comprise particular program channel or guide content. Controller 115 creates a master set of themes and topics mapping the SPG, DPG and IPG information to a corresponding category in the master set. For example, the master  
15 set may contain an encompassing topic-theme of 'movies-comedy' to which is mapped both, a) the DPG topic-theme of 'movie-parodies', and b) the IPG Internet topic-theme of 'movie-synopsis index' (an index of web pages). In collating the guide information, controller 115 determines the topic and theme categories of the  
20 data in the SPG, DPG and IPG from pre-determined theme-topic codes. The SPG, DPG and IPG theme and topic codes together with equivalence mapping information for converting codes of one service provider, to those of another, are acquired from the SPG or User defined data input to processor 25 or are pre-stored in  
25 internal memory within controller 115. Controller 115 assembles the collated SPG, DPG and IPG packets according to the categories defined by the master set of themes and topics. The assembled collated SPG, DPG and IPG data is stored by controller 115 in internal memory for use in forming a composite program guide for  
30 display.

          Controller 115 also forms MPEG compatible non-displayed information, associated with the displayed composite program guide. The non-displayed information includes composite program map, conditional access and network information. This  
35 non-displayed information is required to support identification, assembly and decoding of the packets comprising the composite program guide and the associated program content. The

10

conditional access information governs access to programs based upon User entitlement. The network information defines physical network parameters such as satellite transmission channel frequencies and transponder channels, for example.

5           Controller 115 forms composite program map information for the composite program guide that maps the SPG, DPG and IPG themes and topics to the master set of themes and topics. The composite program map also associates data identifiers (e.g. PID values) with individual packetized datastreams that  
10 constitute programs listed in the composite program guide. The composite program map information may also include a dedicated indicator to denote that a particular program has associated Internet web page information available. In forming composite program map information, controller 115 examines the SPG, DPG  
15 and IPG information for data identifier omissions, redundancies and conflicts. Controller 115 re-numbers existing data identifiers and creates new data identifiers as required to produce MPEG compatible program map information for both the collated program guide information and the associated program content.

20           Controller 115 also forms MPEG compatible conditional access information and network information from corresponding information received in the SPG, DPG and IPG data. The conditional access information includes data such as encryption codes that govern access to programs that are dependent upon user  
25 entitlement. The network information defines physical network parameters such as satellite transmission channel frequencies, transponder channels, and Internet access parameters associated with the composite program guide for display. The composite program map, conditional access and network information  
30 supports assembly, decoding and display of the program content available from the satellite, storage and Internet server sources as well as the composite program guide.

          Controller 115 also includes additional linking data in the non-displayed composite program map, conditional access and  
35 network information. The additional linking data supports the User selectable functions such as Email, telephone, Internet access, fax, video-phone, channel tuning, program recording and home

11

control functions. Home control functions may support User control of lighting air conditioning, heating and burglar alarm operation, for example. The additional linking data associates access data, both with data identifiers (e.g. PIDs) of requested data, and with User selectable menu options in the displayed composite program guide. The access data includes identification codes, communication protocol codes, conditional access codes, Internet access codes e.g. URL codes for web page and Email access as well as telephone and fax numbers. The access data enables processor 25 to communicate with external devices.

In order to generate the composite program guide for display, controller 115 retrieves the assembled and collated SPG, DPG and IPG packet data previously stored in internal memory. Controller 115 both converts the retrieved data to pixel data and formats the converted data for storage in a pixel representative memory map contained in display processor 70. In addition, controller 115 creates User selectable menu options (for User selection of Email, fax etc.) in pixel data form for incorporation in the unit 70 pixel memory map. Controller 115 stores the formatted SPG, DPG and IPG pixel data together with the generated option pixel data in the unit 70 pixel map to form the composite program guide for display.

The composite program guide, combining the SPG, DPG and IPG data and User selectable options, is formatted to be compatible with the linking data in the non-displayed program guide information. For example, a User selectable option in the displayed guide (e.g. for a telephone function) is associated, both with access data for the function (e.g. a telephone number), and with data identifiers (e.g. PIDs for data packets of transmitted and received telephone messages).

Display processor 70 converts the stored and formatted program guide data into conventional luminance and chrominance components. The luminance and chrominance components, together with timing data provided by controller 115, are processed by processor 70 in a conventional manner to form an NTSC signal for display on NTSC compatible image reproduction device 75 e.g. a television or video monitor. Processor 70 may, in

12

another embodiment, provide RGB output data for display by an RGB compatible reproduction device or a high definition television.

Controller 115, in conjunction with processor 55, forms an MPEG compatible datastream of compressed video and audio data containing the composite program guide and program content. Processor 55 separates system information including timing, error and synchronization information from the datastream from unit 45 and diverts it for use by controller 115. Controller 115 applies the system information in controlling processor 55 to provide re-synchronized, collated program and composite program guide data together with synchronization and error indication information for use in subsequent program content data decompression by decoder 65. The composite program guide data provided by processor 55 combines the SPG, DPG and IPG data and User selectable options in a manner compatible with the program map linking information as previously described. The program content data provided by processor 55 is decompressed by MPEG decoder 65 to provide video pixel data and audio output data to processor 70. Display processor 70 processes the video pixel data and audio output data to be suitable for reproduction by unit 75 as previously described.

Figure 2 shows an exemplary displayed composite program guide. Menu features 833-850 show program services and functions. Menu features 833 and 835 show program channels which may be invoked and displayed upon highlighting of the corresponding menu feature using a User selection control such as a remote control directed cursor. If a User highlights feature 833 with the cursor, i.e. selects menu option 833, for example, processor 25 tunes to television channel 107 (A&E™) and displays it on unit 75 using the composite non-displayed program guide information to determine the function activated and associated tuning information (channel frequencies etc.). Similarly, if a User highlights feature 837, processor 25 tunes to receive radio channel FM 13 for audio output on unit 75. Upon highlighting features 840-850, corresponding to Email, telephone, fax and DVD record/playback functions respectively, additional function specific menus become displayed providing further User selection

options. Such function specific menus may provide a User with the ability to edit, store and delete access information including, for example, telephone numbers, Email addresses, Internet addresses, credit card numbers and additional conditional access data.

5           If a User highlights menu features 860-870 specific function tasks are initiated. Upon a User highlighting feature 860, for example, a further menu is displayed prompting the User to enter an Email message to be sent to John Smith at his home via an Internet Email address retrieved from the composite non-  
10 displayed program guide information. Similarly, in response to a User highlighting feature 865, for example, controller 115 (Figure 1) retrieves Jean's home telephone number from internal memory using the composite non-displayed program guide information. Further, controller 115 establishes telephone communication, via  
15 modem 80, with Jean at her home by dialing Jean's home telephone number. Also, upon a User highlighting feature 870, for example, the movie 'Star Wars™' is re-played from DVD unit 90 (Figure 1). The communication between processor 25 and DVD unit 90 is established with access data retrieved from memory  
20 within controller 115 using the composite non-displayed program guide information.

          In addition, the program guide may include one or more icons, such as icon 873 (Figure 2) depicting a home, for example, to indicate whether Internet information such as a 'home  
25 page' is available for a particular program. Further, icon 873, in Figure 2 may change color e.g. from white to green to indicate Internet information is available for a particular program. Alternatively, icon 873 may be a pop-up icon which appears as an indication that Internet information is available for a particular  
30 program. The displayed program guide may be formed to enable a User to request Internet information on a particular program by highlighting the program followed by highlighting the pop-up icon, for example. Home page icons that are present when Internet information is available may also located within or adjacent to  
35 program icons, e.g. icon 859. Further, the home page icon may change color upon User selection of the information by highlighting the home page icon.

Although Internet information may be retrieved upon highlighting a web page icon such as icon 857, in Figure 2, this is exemplary only. Retrieval of Internet information may also be initiated in a variety of other ways. A user may retrieve available  
5 Internet information relating to a program, by highlighting a program icon such as 'Seinfeld™' using icon 859 followed by highlighting Internet icon 810, for example.

Upon User selection of a composite program guide function, controller 115 (Figure 1) determines and applies the  
10 access data associated with both request and response operations involved in the selected function. Controller 115 determines the access data required for the request and response operations from the previously formed non-displayed composite program map, conditional access and network information.

15 Processor 25 acquires information, such as web page data, in response to a User request, in a number of ways, including, for example:

a) In a first configuration, processor 25 accesses web  
20 page data that is continuously transmitted in the satellite broadcast received from decoder 30,

b) In a second configuration, processor 25 acquires web page data that is transmitted in the satellite broadcast  
25 received from decoder 30 in response to an information request to a service provider via telephone line, and

c) In a third configuration, processor 25 both requests information and receives response information on the same  
30 communication link e.g. on the telephone link to server 83.

#### First configuration of Processor 25

In the first configuration, web page data selected by a  
35 User via the displayed program guide is continuously transmitted within the transport datastream input to processor 25 from decoder 30. In this configuration, the composite program map

15

information contains predetermined PID values for the requested web page. Consequently, the requested web page data is retrieved from the input transport stream using the composite program map information without the need for controller 115 to communicate  
5 with a service provider via modem 80. In this configuration, the web information available to a User is limited to the specific information that a service provider continuously transmits to processor 25 using dedicated transmission bandwidth. However, this configuration is simple and offers quick web page access  
10 (since the web data may be stored locally at the encoder by the service provider). This configuration also minimizes the service provider burden of data acquisition and eliminates the need for processor 25 to communicate web page request information to a service provider.

15 The web page information, encoded in HTML™ and Java™, is packetized and formatted in an encoder by the service provider for incorporation into the MPEG transport datastream for transmission. Figure 3 shows a data format, according to the invention, for packetizing Internet data for transmission within an  
20 MPEG compatible datastream. A sequence of HTML™/Java™ web pages (705-720 of Figure 3) is formed by the encoder into non-compressed packets with ancillary information and HTML™/Java™ data (725). The ancillary information includes PID values, a packet count value, and individual web page size (e.g. number of bytes or  
25 image pixel size). The ancillary information may also include: a flag to indicate that a particular transport packet contains web page information; a start code; a web page identification code; an error correction code and a timing parameter suitable for synchronizing web page Internet information with an associated  
30 video or audio program. The web page flag may be used to facilitate identification and separation of the web page information from the MPEG compressed video data. Further, one or more elements of the web page ancillary data may be included within User definable elements of the MPEG transport syntax, such  
35 as within the transport header, or it may be included along with the web page information in the MPEG transport data payload.

16

The response web page information, including a predetermined PID value, is incorporated in the MPEG compatible transport datastream input to processor 25 (Figure 1) by the service provider. The response channel predetermined PID value 5 is also prestored in controller 115 internal memory and incorporated in the composite program map information. As an alternative, the response data PID value and associated program map data may be encoded, for example, in a Channel Information Table (CIT) in a high definition television (HDTV) signal encoded 10 according to the *Digital Television Standard for HDTV Transmission* of April 12 1995, prepared by the United States Advanced Television Systems Committee (ATSC). In such a case, one or more specific pre-determined program channels may be designated to convey web page response information. Further, the 15 PID values of the program channels may be conveyed in a CIT in the composite program map information, for example.

Controller 115 derives the predetermined PID value corresponding to the requested web page response information from the stored composite program map information and loads it 20 into control registers within unit 45. Unit 45 matches the PIDs of incoming packets of web page response data in the transport datastream from decoder 30 with the PID value pre-loaded in the unit 45 control registers. The packets with PID values matching the pre-determined web response PID value are identified as web 25 page response data and are provided by unit 45 to a dedicated buffer in decoder 55. The dedicated buffer in transport decoder 55 holds response data to be decoded by processor 60.

Processor 55 derives system information including timing, error and synchronization information from the 30 datastream from unit 45 and provides it to controller 115. Controller 115 applies the system information in directing processor 55 to provide re-synchronized web page response data from the dedicated buffer in decoder 55 to HTML™/Java™ processor 60. Processor 60 decodes the HTML™ and Java™ encoded 35 web response information and provides web page image representative pixel data for storage in memory within controller 115. Although processor 60 is shown as a separate processor in

17

Figure 1, it may also be implemented within the software of controller 115. Processor 60 comprises the processing functions of a special web browser, including JPEG decompression and Java decoding such as involved in the operation of Netscape Navigator™, for example.

Program content data e.g. a User selected television program channel, within the MPEG compatible transport datastream from decoder 30, is also decoded into pixel representative data by processor 25 in addition to the web page response data. For this purpose, controller 115 determines the PID value of the selected television channel program from the composite program map information and loads it into control registers within unit 45. Unit 45 matches the PIDs of incoming packets of selected television channel program data in the transport datastream from decoder 30 with the PID value pre-loaded in the unit 45 control registers. The packets with PID values matching the pre-determined selected television channel program PID value are identified and provided by unit 45 to a dedicated application buffer in decoder 55.

As previously described for the web page response data, processor 55 derives system information including timing, error and synchronization information from the datastream from unit 45 and provides it to controller 115. Controller 115 applies the system information in directing processor 55 to provide re-synchronized program channel content data from the application buffer in decoder 55 to MPEG decoder 65. The MPEG compatible program channel content data is decompressed by MPEG decoder 65 to provide video pixel data and audio output data to display processor 70. The video pixel data from decoder 65 is stored in a pixel representative memory contained in display processor 70.

Controller 115 retrieves the web page image pixel data from internal memory and formats it for storage as an overlay in the pixel representative memory contained in display processor 70. As such a merged display combining the web page response data and program channel content is formed within the pixel memory of processor 70. The relative proportions and sizes of the web page image and channel content image within the resultant

18

composite image, formed in the processor 70 pixel memory, may be varied by controller 115 in response to internal programmed instruction or external, e.g. User, command. The relative proportions may be varied so that either the web page image or 5 channel content image contributes between 0-100% of the resultant composite image.

In order to adjust the proportion of the composite image contributed by the web page data, controller 115 scales the web page image pixel data by a conventional interpolation 10 process. Alternatively, the data may be scaled by a separate video processing integrated circuit operating in conjunction with controller 115. The resulting scaled web page image is stored within the processor 70 pixel memory by controller 115. The stored web page image represents an overlay image with respect 15 to the program channel content image. In order to adjust the location of the web page image data within the composite image, controller 115 determines the addresses corresponding to the desired memory locations from internal memory map data and stores the scaled web page image data at the desired memory 20 locations. As previously explained, display processor 70 converts the formatted composite image data into conventional luminance and chrominance components. Further, processor 70 processes the luminance and chrominance components, together with timing data provided by controller 115, in a conventional manner to form 25 an NTSC signal for display on NTSC compatible image reproduction device 75.

### Second configuration of Processor 25

30 In the second configuration, processor 25 of Figure 1 acquires web page data that is transmitted in the satellite broadcast received from decoder 30 in response to an information request to a service provider via a telephone line. Upon a User requesting web page data, e.g. by highlighting web page icon 857 35 in Figure 2, controller 115 (Figure 1) uses the request access data (telephone number, requested web page identifier code (e.g. URL)

and conditional access data) to establish communication with the satellite broadcast service provider.

Prior to establishing communication with the service provider, controller 115 determines from conditional access information whether access to the requested web page information is authorized. Authorization may be determined directly from the program guide conditional access information or indirectly from a User entitlement device such as a smart card (not shown to simplify the drawing) within processor 25. If access is authorized, controller 115 establishes telephone communication with the satellite broadcast service provider by dialing a telephone number via modem 80 and transmitting request information e.g. requested web page identifier code (such as a URL) and user entitlement code. The service provider incorporates the requested web page information in the transport datastream transmitted to processor 25 via antenna 10, processor 20 and decoder 30. Controller 115 uses the response access data (PIDs of the web page data, response program channel number and transponder number) to identify and assemble the web page packets in the transport stream as described for the first configuration of processor 25.

The PID values of the response web page information and corresponding program map information may be communicated between service provider and processor 25 in a variety of ways and in a variety of data formats. The PID values and program map information may be conveyed, for example, in accordance with proprietary or custom requirements of a particular system such as within MPEG user definable data elements or within non-MPEG data such as within the vertical blanking interval (overscan region) of a broadcast television signal. Further, the PID values allotted to the web information may also be transmitted to processor 25 in supplemental program guide information. As another alternative, the PID values to be used for response data may be determined by a service provider from information transmitted from processor 25.

### Third configuration of Processor 25

In a third configuration, processor 25 both requests  
5 information and receives response information on the same  
communication link e.g. on the telephone link to server 83 or  
connection service 87, via modem 80. In this configuration,  
controller 115 requests Internet web page information by  
highlighting icon 857 (Figure 2), for example. Whereupon  
10 controller 115 (Figure 1) uses request access data (telephone  
number and URL code and conditional access data) to establish  
Internet access and request web page data at the URL address via  
modem 80 and server 83. Controller 115 determines whether the  
requested Internet access is authorized from conditional access or  
15 smart card User entitlement information as described in  
connection with the second configuration of processor 25. If  
authorized, controller 115 establishes telephone communication  
with a service provider via server 83 by dialing a telephone  
number using modem 80 and transmitting the Internet URL  
20 address code and user entitlement code, for example, as  
previously described. Controller 115 uses response access data  
(including Transmission Control Protocol/Internet Protocol  
(TCP/IP) identification data) determined from the composite  
program map information to identify and assemble the web page  
25 TCP/IP packets containing the web page HTML and associated  
JAVA data (and other data e.g. JPEG, GIF, TIF type data) in the  
response datastream from server 83.

The response web page TCP/IP packets are buffered  
within modem 80 and provided to HTML™ processor 60 under  
30 command of controller 115. Processor 60 decodes the HTML™ and  
Java™ encoded web response information and provides web page  
image representative pixel data for storage in memory within  
controller 115. Controller 115 retrieves the web page image pixel  
data from internal memory and formats it for storage as an  
35 overlay in the pixel representative memory contained in display  
processor 70 for reproduction by unit 75 as a merged display, as  
previously described. In this configuration, processor 25 supports

21

full Internet access via server 83 using the displayed program guide. For example, upon a User highlighting icon 810 followed by icon 830 (Figure 2) controller 115 (Figure 1) executes web page browser functions and displays either a custom web page browser or a standard browser display such as Netscape Navigator™ through which full Internet access is available.

Alternatively, in the third configuration, processor 25 may support a limited Internet service. In this case, access to the Internet network via server 83 is under the control of a service provider that allows only indirect Internet access. The service provider provides collated web page information for display compatible with the displayed composite program guide. The service provider stores a limited number of web pages locally within server 83 that are accessible by processor 25 using the composite program map information which provides an index to the available web pages and their corresponding predetermined PIDs. Alternatively, the service provider may alter the selection of web pages available from server 83 and periodically provide updated compatible supplemental program guide information to processor 25 via the satellite broadcast datastream.

The supplemental program guide information enables processor 25 to form an updated displayed guide together with compatible program map and other access information enabling a User to access the updated web information. By storing the web page Internet information locally in server 83 the service provider retains control of the Internet content available to a User and is able to bill the User for the material provided. Also, the local storage of the web page information in server 83 provides a User with faster access to the information without the full delay associated with normal Internet access. Further, the burden on processor 25 of communicating information requests to external devices is minimized in that only a limited quantity of Internet information may be requested and processor 25 need only communicate with local servers such as server 83. It is to be noted that modem 80 may also be a wide bandwidth communication modem such as a cable modem. In which case, processor 25 may

## 22

decode both web page data and broadcast video program data for display from a cable program source via modem 80.

Controller 115 employs the method shown in Figure 4 to produce a displayed program guide by processing and 5 formatting received program guide information that already includes User selection menu options. The process of Figure 4 does not require processor 25 to form User selection menu options and may be employed by processor 25 in its first configuration, for example. In step 205, following the start at step 200, processor 25 10 receives a transport datastream from decoder 30 that incorporates User selectable menu options for display as part of the displayed program guide. The User selectable options support User initiation of communication functions such as Email, telephone, Internet access, fax, video-phone, channel tuning, program recording and 15 home control functions.

The data received in step 205 also includes additional linking data in the program guide information. The additional linking data comprises program map, conditional access and network information and associates access data with the User 20 selectable menu options in the displayed program guide. The access data includes, identification codes, communication protocol codes, conditional access codes, Internet access codes e.g. URL codes for web page and Email access as well as telephone and fax numbers. The additional linking data enables processor 25 to 25 assemble, decode and display the program content and program guide information in the transport stream from decoder 30. The access data enables processor 25 to communicate with external devices and includes different address representative codes corresponding to addresses of different information sources. In 30 step 210, controller 115 uses predetermined linking data PID values stored in internal memory in directing processor 25 to identify and capture the linking and access data from the received program guide information. The captured linking data is assembled, formatted and stored by controller 115 in internal 35 memory in step 215. Also, in step 210, additional linking data such as Internet or Email addresses or telephone numbers may be entered by a User via an entry device such as a remote control

## 23

unit and the additional data is incorporated in the received linking data by controller 115.

The program guide information containing the User selectable options, is formatted for display by controller 115 in conjunction with display processor 70 within processor 25 in step 220, as previously described in connection with Figure 1. In step 225, display processor 70 converts the stored and formatted program guide data into conventional luminance and chrominance components. The luminance and chrominance components, together with timing data provided by controller 115, are processed by processor 70 for display on reproduction device 75. The process of Figure 4 terminates at step 230.

Controller 115 (Figure 1) employs the method shown in Figure 5 to produce a program guide in a video decoder from information received from a plurality of sources. The formed guide supports User selectable communication functions e.g. Internet access, Email, fax etc. . In step 305, following the start at step 300, controller 115 acquires satellite program guide (SPG) information from the satellite broadcast transport stream received by processor 25 from decoder 30. In step 310, controller 115 acquires DVD program guide (DPG) information from storage device 90 via interface 95. Controller 115 acquires, collates and formats the SPG and DPG by accessing and assembling respective data packets to produce SPG and DPG representative pixel data for storage as a composite program guide in the unit 70 pixel map, as previously described in connection with Figure 1. The SPG and DPG information includes linking and access data in the form of program map, conditional access and network information. In other configurations, processor 25 applies the principles detailed herein to form a composite program guide including program guide information derived from a source such as a terrestrial broadcast source, a cable broadcast source, a computer source, a radio transmission source and a source accessed via telephone lines.

In step 315, controller 115 creates User selectable menu options for display (for User selection of Internet access, Email, fax etc.) in pixel data form for incorporation in the unit 70

24

pixel memory map. In step 315, controller 115 also creates User determinable menu options that enable a User to customize his program guide to include an icon that performs a specific User requested function, for example, a User may require an icon that  
5 accesses a specific Internet site or results in a display of all received messages. Controller 115 responds to commands entered via a data entry device e.g. a remote control unit or keyboard in creating the User determinable menu option in accordance with programmed instructions.

10 Controller 115, in step 320, examines the SPG and DPG information for data identifier (e.g. PID) omissions and conflicts. In step 325, controller 115 re-numbers existing data identifiers and allocates new data identifiers as required to produce compatible program map information for both the collated program guide  
15 information and the associated program content. In step 330, controller 115 forms composite program map, conditional access and network information for the composite program guide in the manner described in connection with Figure 1.

The composite program map is formed to enable  
20 processor 25 to perform the communication functions selectable via the composite program guide. For this purpose, the composite program map associates a communication function PID and menu option (e.g. web page, Email, fax icon) with the different address representative codes corresponding to the addresses of the  
25 different information sources. In step 330, controller 115 also incorporates User entered data into the composite program map, conditional access and network information. This data may include items such as an Email address, a telephone/fax number, an Internet web page link address, a credit card number etc. The  
30 User enters this data to processor 25 via a device such as a remote control or keyboard. Controller 115, in step 335, formats the SPG and DPG pixel data together with the menu option pixel data in the unit 70 pixel map created in step 315 to form a composite program guide for display.

35 The composite program guide information containing the User selectable menu options is formatted for display in step

25

340, and output in step 345 as previously described in connection with Figure 1. The process of Figure 5 terminates at step 350.

Controller 115 (Figure 1) employs the process of Figure 6 to automatically acquire and collate program guide information 5 from a plurality of sources to form a composite program guide for display. In step 405, following the start at step 400, controller 115 acquires and stores satellite program guide (SPG) information from the satellite broadcast transport stream received by processor 25 from decoder 30. Controller 115, in step 415, 10 automatically initiates communication with DVD storage device 90 (Figure 1), via interface 95. The communication is initiated upon power-up of processor 25 in response to pre-stored hardware configuration information defining the peripheral devices that are attached to processor 25 and the associated communication 15 protocols. This information may be contained within the received program guide information, or may be stored within processor 25 at manufacture, or may be determined locally by processor 25 or may be determined through a combination of these methods. The local determination of hardware configuration by processor 25 20 may be accomplished either by peripheral interrogation initiated by controller 115, or by User data entry of hardware configuration data.

In alternative embodiments, communication may be automatically initiated upon conditions such as, a) User command 25 via a program guide option selection, for example, b) peripheral interrogation initiated by controller 115 on a periodic or intermittent basis, or c) detection of a new or changed electrical connection of processor 25 to a peripheral device such as DVD device 90.

30 Controller 115 initiates communication with DVD unit 90 via interface 95 using communication protocol codes, identification codes, entitlement codes and conditional access codes retrieved from the access data within the received program guide information. In step 420, controller 115 directs processor 25 35 to acquire and assemble the DVD program guide (DPG) information derived from DVD storage device 90 via interface 95 in the manner previously described in connection with Figure 1. In step

26

425, controller 115 collates the SPG and DPG information by theme and topic by mapping the SPG and DPG information to corresponding theme and topic categories in a master set, also as described in connection with Figure 1. Further, in step 425, 5 controller 115 collates the SPG and DPG information by source and allocates a different color attribute to programs and program icons from different sources. In addition, controller 115 creates menu options permitting a User to sort by source and color.

Figure 7 shows a black and white representation of a 10 color Program Guide display format, according to the invention, showing menu options created by controller 115 permitting a User to collate programs by source and color attribute. Source icons 905-925 are associated with off-air broadcast, cable, radio, satellite and storage (e.g. DVD source 90 - Figure 1) respectively. 15 Source icons 930-950 are associated with Email, telephone, videophone, fax and Internet function sources respectively. Upon a User highlighting source icon 905, for example, a program guide is displayed showing off-air broadcast programs and associated icons. Similarly, upon a User highlighting source icon 930, for 20 example, a program guide is displayed showing Email icons via which a User may activate menus for initiating composition and sending of Email messages and reading and deleting of messages received.

Icon 900 is a "rainbow" sort icon showing a spectrum 25 of discrete color blocks represented by shades of gray in the black and white program guide depiction of Figure 7. The color choices of icon 900 may alternatively be arranged as a continuous color spectrum or selected range of colors in a single or a number of discrete color blocks. Upon a user highlighting a particular color 30 within icon 900, programs from the source attributed with that particular color are displayed. For example, assuming in step 425 controller 115 attributes the color purple to the DVD source device 90, then upon a user highlighting the color purple within icon 900, the movies available from DVD device 90 become displayed as a 35 program guide. Alternatively, the color collation scheme may be used to identify programs by other criteria than source. Color may be used as an attribute to identify programs by theme or topic, for

27

example, in which case a display of movies available for viewing from all sources may be identified by highlighting a red color within icon 900, for example. In addition, program guide data may be collated by attributes other than color. For example, programs 5 from different sources may be attributed with different types of shading or different icon shapes and geometrys.

Continuing with the process of Figure 6, in step 430, controller 115 forms a composite program guide for display from the collated SPG and DPG information in a manner similar to that 10 described in connection with Figure 1. Controller 115 also, in step 425, creates associated User selectable menu options for display including the User selectable program guide options for sorting by source and color. The created menu options are incorporated by controller 115 in step 430 in a composite program guide for 15 display as exemplified in Figure 7. In step 435, controller 115 formats the composite program guide information for display as previously described in connection with Figure 1. The process of Figure 6 terminates at step 440.

Controller 115 (Figure 1) employs the process of Figure 20 8 to acquire web page information requested by a video receiver User via a selection made from options on a displayed program guide. In step 505, following the start at step 500, controller 115 retrieves access data in the form of a telephone number and Internet URL code, for example, from memory in response to a 25 User selection of a web page made via a displayed program guide. The access data associated with the particular User selection is determined from a program guide database using program map information that links all data associated with a particular program or program guide function.

30 In step 515, controller 115 directs processor 25 to establish a request communication link with server 83 by dialing the retrieved telephone number using modem 80. Also, in step 515, processor 25 encodes and transmits additional access data such as the Internet URL code using the protocol required for 35 communication on the request communication link. The required protocol is determined from the program map information. In step 520, controller 115 directs processor 25 to receive and decode an

input signal received on a response communication link. Controller 115 directs processor 25 in identifying and retrieving the response web page information from the input signal in steps 525 and 530. Different methods of retrieving response data from the input signal are employed by processor 25 in steps 525 and 530. The selected method depends on whether or not the response communication link is the same link used for the web page data request. The methods used in identifying and retrieving the response data are similar to those previously described in connection with the three configurations of processor 25. Controller 115 applies the appropriate configuration method in identifying the response web page data in the input signal, in step 525. For this purpose, controller 115 uses data identifiers determined from program map information that associates the identifiers with the User program guide selection. Controller 115, in step 535, formats the response web page information for display and the Figure 8 process ends at step 540.

Controller 115 (Figure 1) employs the process of Figure 9 for decoding both input Internet information and compressed video data to form a composite video output for display. Following the start at step 600, controller 115, in step 605, determines packet identifiers for User requested Internet data and compressed image data from program map information. In step 607, controller 115 determines whether access to the compressed video data and the requested Internet data is authorized from conditional access or smart card User entitlement information as previously described in connection with the third configuration of processor 25.

If access is authorized, controller 115, in step 610, identifies the web page TCP/IP packets containing the web page data in a response datastream from server 83. Similarly, if access is authorized, controller 115, in step 615, identifies the compressed video data packets containing a User selected video program in an input transport stream from decoder 30 to processor 25. Controller 115 identifies the web page and compressed video data packets in a similar manner to that described in connection with Figure 1.

29

In step 617, controller 115 directs processor 25 (Figure 1) to decrypt Internet or compressed video data if it is encrypted. Controller 115 in step 620, directs processor 25 in decoding the identified Internet web page data using HTML™ processor 60. Controller 115 in step 625, directs processor 25 in decompressing the identified compressed video data using MPEG decoder 65. The resultant decoded web page data and decompressed video data is merged, formatted and displayed on unit 75 using display processor 70 under the direction of controller 115 in step 630. The process of Figure 9 terminates at step 640.

The architecture of Figure 1 is not exclusive. Other architectures may be derived in accordance with the principles of the invention to accomplish the same objectives. Further, the functions of the elements of processor 25 of Figure 1 and the process steps of Figures 4-6, 8 and 9 may be implemented in whole or in part within the programmed instructions of a microprocessor. In addition, the principles of the invention apply to any form of MPEG or non-MPEG compatible electronic program guide. Further, the principles of the invention apply to communication on any form of communication link including via cable, infra-red, radio, microwave, and via a computer network. In addition, it is to be noted that the formation of the composite program guide as described herein may be performed at a location remote from a video receiver and accessed by the receiver via a communication network.

30  
CLAIMS

1. In a video decoder system for receiving program guide information from a first source, a method for collating  
5 program guide information, comprising the steps of:

- a) displaying a selectable program guide menu icon;
- b) collating a category of program guide information items from said first source by a display attribute in response to selection of said menu icon, said display attribute being allocated  
10 to said category of program guide information items and said display attribute being common to both said category and to said menu icon; and
- c) displaying said collated program guide information items.

15

2. A method according to claim 1, wherein  
said display attribute represents at least one of a) color, b) shading, and c) geometry.

20

3. A method according to claim 1 wherein, in said collating step

said category of program guide information items includes items associated with at least one of a) a particular source, b) a particular function and c) particular program content.

25

4. A method according to claim 3 wherein, in said collating step

said function category includes items associated with at least one of a) Email, b) fax, c) telephone and d) video phone.

30

31

5. A method according to claim 3 wherein, in said collating step

said content category includes items associated with at least one of a) program theme and b) program topic.

5

6. A method according to claim 1 further including the steps of

allocating a plurality of display attributes to a corresponding plurality of categories of program guide information items, and

10 hierarchically collating said categories of program guide information items.

7. A method according to claim 1 further including the 15 steps of

receiving program guide information from a second source;

allocating a display attribute to a category of program guide information items from said first source and said second 20 source; and

collating said category of program guide information items from said first source and said second source by said display attribute in response to selection of said menu icon.

25 8. A method according to claim 1 further including the step of

forming program map information for associating said display attribute with programs listed in said program guide items.

30

9. A method according to claim 1 further including the step of

forming program map information for associating said display attribute with said displayed program guide menu icon.

10. In a video decoder system for receiving program guide information from a first source and a second source, a method for collating program guide information from a plurality of sources, comprising the steps of:

- a) allocating a new data identifier to a program guide information item from said second source;
- b) forming composite program map information associating said new data identifier with a program listed in said program guide item from said second source;
- c) retrieving said second source program guide item from memory using said new data identifier; and
- d) displaying said second source program guide item.

11. A method according to claim 10, further including the step of removing duplicated and redundant program guide information items prior to said allocating step.

12. A method according to claim 10, further including the step of forming composite program map information associating a first code identifying a first program category with data identifiers of a plurality of program guide items.

13. A method according to claim 12, further including the step of using said first code for identifying program guide information items associated with at least one of, a) a particular source, b) a particular function and c) particular program content.

14. A method according to claim 12, further including the step of forming composite program map information associating a second code identifying a second program category with data identifiers of a second plurality of program guide items.

33

15. A method according to claim 14, further including the step of

hierarchically sorting said program guide information items by category using said first code and said second code.

5

16. A method according to claim 15, wherein said first and second categories correspond to program theme and topic respectively.

10

17. In a video decoder system for receiving program guide information from a first source containing a first code identifying a program category, a method for collating program guide information from a plurality of sources, comprising the steps of:

15

a) converting said first code to a second code in accordance with equivalence mapping information for allocating a category in a master set of program categories to said received program category;

b) sorting and merging program guide information from said first source and a second source according to said master set of program categories; and

c) displaying said sorted and merged program guide information.

25

18. A method according to claim 17, further including the step of receiving said equivalence mapping information.

19. A method according to claim 17, further including the step of

30

retrieving said equivalence mapping information from said program guide information from said first source.

20. A method according to claim 17, wherein  
said equivalence mapping information is pre-stored in  
decoder memory and said method including the further step of.  
5       retrieving said equivalence mapping information from  
said decoder memory.





FIGURE 1.

2/9



3/9

FIGURE 3





FIGURE 4

4/9



5/9

FIGURE 5






FIGURE 6

6/9




7/9

FIGURE 7




8/9

FIGURE 8



9/9

FIGURE 9



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 97/17031

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H04N7/173

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04N G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 13368 A (STARSIGHT TELECAST INCORPORATED) 10 April 1997 see the whole document ---	1-17
Y	US 5 589 892 A (KNEE R. ET AL) 31 December 1996 see column 9, line 50 - column 13, line 48 see column 17, line 25 - column 21, line 35 see column 27, line 21 - column 37, line 51 see column 43, line 53 - line 55 ---	1-17
Y	WO 96 33572 A (STARSIGHT TELECAST INCORPORATED) 24 October 1996 see page 2, line 9 - page 5, line 19 --- -/--	1-17

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

2 February 1998

Date of mailing of the international search report

12/02/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Verschelden, J

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 97/17031

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 96 09721 A (TV GUIDE ON SCREEN) 28 March 1996 see page 7, line 15 - page 12, line 14 ---	1-17
A	WO 95 33338 A (BELL ATLANTIC NETWORK SERVICES INC.) 7 December 1995 see page 6, line 27 - page 36, line 35 ---	1-17
A	EP 0 746 119 A (MITSUBISHI DENKI KABUSHIKI KAISHA) 4 December 1996 see column 9, line 7 - line 35 see column 30, line 53 - column 31, line 20 see column 32, line 12 - column 34, line 10 ---	1-10
P,X	WO 97 28499 A (AWARD SOFTWARE INTERNATIONAL INC.) 7 August 1997 see the whole document ---	1-17
E	WO 97 41690 A (AWARD SOFTWARE INTERNATIONAL INC.) 6 November 1997 see the whole document -----	1-17

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/17031

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9713368 A	10-04-97	AU 7387196 A	28-04-97
US 5589892 A	31-12-96	AU 6258596 A	30-12-96
		WO 9641478 A	19-12-96
		AU 5572996 A	18-11-96
		WO 9634491 A	31-10-96
		US 5585866 A	17-12-96
WO 9633572 A	24-10-96	US 5550576 A	27-08-96
		AU 5443996 A	07-11-96
		US 5684525 A	04-11-97
WO 9609721 A	28-03-96	US 5559548 A	24-09-96
		AU 3681895 A	09-04-96
		CA 2200348 A	28-03-96
		EP 0782806 A	09-07-97
WO 9533338 A	07-12-95	US 5635979 A	03-06-97
		AU 2657995 A	21-12-95
		US 5666293 A	09-09-97
EP 746119 A	04-12-96	JP 9051297 A	18-02-97
WO 9728499 A	07-08-97	NONE	
WO 9741690 A	06-11-97	NONE	